

INTRA V50 GOLD PICKUP

SUCCESS KA MANTRA

INTRA WALON KI SUNO

Apne Business
ko Aage Badhao



**1700 kg
PAYLOAD**

AB UTHAYE AUR
BHI ZYADA



**Strong
Chassis**



**High
Pulling Power**



**Mileage Pays
before Resale Value**



**FOOD
GRAINS**



**CEMENT
BAGS**



**MILK
CANS**



**FRUITS AND
VEGETABLES -
CRATES**



**FRUITS AND
VEGETABLES -
BAGS**



**Longer Load Body
2 960 mm (9'8")**

**1700 kg MORE
PAYLOAD**



**5.18 M² LARGER
LOAD BODY**



**10 LEAF SPRING
SUSPENSION**



FLEET EDGE



Enhanced Payload with Better Stability

SPECIFICATIONS

Intra V50 Gold CX/LX/VX

Engine Type	1.5 Common Rail Turbo Intercooled Diesel - 4 cylinder
Engine Capacity CC	1 497cc
Max Engine Output	60 kW (80 hp) 4 000 r/min
Max Torque	220 Nm @ 1750-2 500 r/min
Gearbox	G5220 Synchromesh 5F + 1R
Clutch Dia (mm)	240
Steering	Hydraulic Power Steering
Front suspension	Parabolic leaf spring - 2 leaves
Rear suspension	Semi-elliptical leaf springs - 10 leaves
Front brakes	Disc brake
Rear brakes	Drum brake
Tyres	215/75 R15
Load Body	2 960 X 1 620 X 400 (CX), 2 960 X 1 750 X 400 (LX, VX)
Turning Circle Radius	6 050 mm
Wheel Base (mm)	2 600
Length (mm)	4 734
Width (mm)	1 694 (Without mirror)
Height (mm)	2 014
GVW (kg)	3 160 (CX,LX), 3 210 (VX)
Kerb Weight (kg)	1 455 (CX), 1 460 (LX), 1 510 (VX)
Payload	1 705 (CX), 1 700 (LX, VX)
Top Speed	80 km/h
Seating capacity	D+1
Warranty (On Driveline)	3 years or 100 000 km* (Whichever is earlier)
Fuel Tank	35 L
Ground Clearance	193 mm

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.

***T&C Apply**